


INSTALLING FOG LIGHT

1. ATTACH FOG LIGHT TO THE ANGLE ALUMINUM BRACKET USING THE SUPPLIED HARDARE AND OEM HARDARE:

SUPPLIED: 3/8" X 1" GR.5 HEX BOLT (2) 3/8" GR.C STOVER NUT (2) 3/8" GR.2 FLAT WASHER (4)

OEM HARDWARE: M10 HEX BOLT (2) M10 WASHER (2)



	MAGNUM TRAILER	FRACTIONS CHART				UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES		sheet name FOG LIGHT	17279 ON	17279 ON 2021 WESTERN STAR 49X SBA (LOGGER)				
	EQUIPMENT INC.	1/32 .03125 1/16 .0625 3/32 .09375 1/8 .125 5/32 .15625 3/16 .1875 7/32 .21875 1/4 .25	9/32 .28125 5/16 .3125 11/32 .34375 3/8 .375 13/32 .40625 7/16 .4375 15/32 .46875 1/2 .5	17/32 .53125 9/16 .5625 19/32 .59375 5/8 .625 21/32 .65625 11/16 .6875 23/32 .71875 3/4 .75	25/32 .78125 13/16 .8125 27/32 .84375 7/8 .875 29/32 .90625 15/16 .9375 31/32 .96875	TOLERANCES ARE: FRACTIONS ANGLES +/- 1/16" +/- 1°		CURRENT CUSTOMER	STOCK NUMBER	VENDO	VENDOR NUMBER		WEIGHT - LB. 316.	
1						.XX" +/- 0.03"	.XXX" +/- 0.005"	WO#	MD	DRAWN DATE 9/20/2021	CHECKED BY LS	CHECKED DATE 9/20/2021	B	
						DIMENSIONS TO	SHARP POINTS	scale 2:3	MODELLER		A-59158	NUMBER O	OF SHEETS	

59158